

## Section 1 - Product and Company Identification

|                            |  |
|----------------------------|--|
| <b>Material Name</b>       | <ul style="list-style-type: none"><li>• <b>TopShield #33 All Weather Rubberized Cement</b></li></ul>                     |
| <b>Chemical Category</b>   | <ul style="list-style-type: none"><li>• Mixture</li></ul>  |
| <b>Product Code</b>        | <ul style="list-style-type: none"><li>• TS-3301</li></ul>  |
| <b>Product Description</b> | <ul style="list-style-type: none"><li>• Rubberized Roof Cement</li></ul>   |
| <b>Product Use</b>         | <ul style="list-style-type: none"><li>• Roofing</li></ul>  |
| <b>Synonyms</b>            | <ul style="list-style-type: none"><li>• Asphalt Based Roof Cement</li></ul>  |
| <b>Manufacturer</b>        | <ul style="list-style-type: none"><li>• APOC</li></ul> <p>4161 East 7th Avenue<br/>Tampa, FL 33605<br/>United States</p> |

### Telephone

- General** • 813-248-2101  
**Emergency** • 800-424-9300  
**Technical** • 813-248-2101

Last Revision Date • 1/11/2018

## Section 2 - Hazards Identification

### GHS HAZARDS AND PRECAUTIONS

#### SIGNAL WORD: WARNING!

*Flammable liquid (paste) and Vapor. Contains Combustible Petroleum Distillates. Harmful or Fatal if swallowed. Keep away from heat, sparks, and open flame. Avoid prolonged breathing of vapor and use only in adequate ventilation. Repeated and prolonged overexposure to solvent vapor may cause brain and nervous system damage, respiratory tract irritation, dizziness, or loss of consciousness. May cause skin and eye irritation.*

|                         |  |
|-------------------------|--|
| <b>Prevention</b>       | Avoid breathing dust, fume, gas, mist, vapors and/or spray. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. Use personal protective equipment as required. Keep out of reach of children.  |
| <b>Response</b>         | IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| <b>Storage/Disposal</b> | Store in a closed container. Store in a well-ventilated place. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.   |



- Physical Form** • Liquid
- Color** • Black
- Odor** • Mild Hydrocarbon.
- Flash Point** • 105°F(40.6°C) CC (Closed Cup)
- UEL** • 6 %
- LEL** • 0.9 %
- OSHA(HCS2012)** • Flammable Liquids - Category 3, Specific Target Organ Toxicity Repeated Exposure - Category 2, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 1A
- WHMIS** • Combustible Liquids - B3, Other Toxic Effects - D2A, Other Toxic Effects - D2B
- GHS** • Flammable Liquids - Category 3, Specific Target Organ Toxicity Repeated Exposure - Category 2, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 1A

**Potential Health Effects**

**Inhalation**

**Acute (Immediate)** • May cause irritation. Excessive breathing of high vapor concentration can cause possible unconsciousness and even asphyxiation.

**Chronic (Delayed)** • Refer to other information found in Section 11-Toxicology.

**Skin**

**Acute (Immediate)** • May cause irritation.

**Chronic (Delayed)** • Repeated and prolonged exposure may cause dermatitis.

**Eye**

**Acute (Immediate)** • May cause irritation.

**Chronic (Delayed)** • Repeated and prolonged exposure may cause irritation.

**Ingestion**

**Acute (Immediate)** • May be harmful or fatal if swallowed.

**Chronic (Delayed)** • Repeated and prolonged exposure may be harmful.

**Carcinogenic Effects** • **This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 - Toxicological Information for more details.**

| Carcinogenic Effects |           |  |                     |
|----------------------|-----------|--|---------------------|
|                      | CAS       | IARC   | NTP                 |
| Asphalt              | 8052-42-4 | Group 2B-Possible Carcinogen<br>Group 3-Not Classifiable | Under Consideration |

**Section 3 - Composition/Information on Ingredients**

| Hazardous Components |  |               |  |  |
|----------------------|--|---------------|--|--|
| Chemical Name        | Identifiers  | %(weight)     | LD50/LC50  | Classifications According to Regulation/Directive  |
| Asphalt              | CAS:8052-42-4<br>UN:NA1999<br>EINECS:232-490-9           | 40% TO<br>60% | Ingestion/Oral-Rat LD50<br>• >5000 mg/kg<br>Inhalation-Rat LC50 •<br>>94.4 mg/m <sup>3</sup> | WHMIS: Other Toxic Effects - D2A<br>UN GHS: Carc. 2; Eye Irrit. 2A; Skin Irrit. 2<br>EU DSD/DPD: |
| Mineral Spirits      | CAS:8052-41-3<br>EC Number:232-489-3<br>EINECS:232-489-3 | 15% TO<br>30% |  | EU DSD/DPD: Carc.Cat.2; R45 Muta.Cat.2;<br>R46 Xn; R65   |
| Kaolin               | CAS:1332-58-7  | 5% TO         |  | UN GHS: Eye Irrit. 2A; STOT RE 2   |

|   |  |                 |  |  |
|---|--|-----------------|--|--|
|   |  | 15%             |  | <b>EU DSD/DPD:</b> Irritant(Xi); R36/37  |
| Cellulose   | <b>CAS:</b> 9004-34-6<br><b>EINECS:</b> 232-674-9  | 6% TO<br>10%    | Ingestion/Oral-Rat LD50<br>• >5 g/kg<br>Inhalation-Rat LC50 •<br>>5800 mg/m <sup>3</sup> 4 Hour(s)<br>Skin-Rabbit LD50 • >2<br>g/kg            | <b>WHMIS:</b> Other Toxic Effects - D2B<br><b>UN GHS:</b> Eye Irrit. 2A; Skin Irrit. 2<br><b>EU DSD/DPD:</b>   |
| Hydrated aluminum-<br>magnesium silicate          | <b>CAS:</b> 12174-11-7   | 5% TO<br>10%    |  | <b>WHMIS:</b> Other Toxic Effects - D2A<br><b>UN GHS:</b> Carc. 2; STOT RE 2<br><b>EU DSD/DPD:</b> Carcinogen 2(Carc.Cat.2);<br>R49; Toxic(T)  |
| Solvent naphtha<br>(petroleum), light<br>aromatic | <b>CAS:</b> 64742-95-6<br><b>EC Number:</b> 265-199-<br>0<br><b>EINECS:</b> 265-199-0                    | 1% TO<br>5%     |  | <b>UN GHS:</b> Asp. Tox. 1; Carc. 1B<br><b>EU DSD/DPD:</b> Carc.Cat.2; R45Muta.Cat.2;<br>R46Xn; R65  |
| Styrene/Butadiene<br>Polymer                      | <b>CAS:</b> 9003-55-8  | 1% TO<br>5%     |  |  |
| Quartz  | <b>CAS:</b> 14808-60-7<br><b>EC Number:</b> 238-878-<br>4<br><b>EINECS:</b> 238-878-4                    | 1% TO<br>2%     |  | <b>UN GHS:</b> Carc. 1A; STOT RE 1<br><b>EU DSD/DPD:</b> Carcinogen 1(Carc.Cat.1);<br>R49  |
| 1,2,4-<br>Trimethylbenzene                        | <b>CAS:</b> 95-63-6<br><b>EC Number:</b> 202-436-<br>9<br><b>EINECS:</b> 202-436-9                       | 0.5% TO<br>1.5% | Ingestion/Oral-Rat LD50<br>• 5 g/kg<br>Inhalation-Rat LC50 •<br>18000 mg/m <sup>3</sup> 4 Hour(s)<br>Ingestion/Oral-Mouse<br>LD50 • 6900 mg/kg | <b>UN GHS:</b> Acute Tox. 4 (Inhalation); Aquatic<br>Chronic 2; Flam. Liq. 3; Eye Irrit. 2A; Skin<br>Irrit. 2; STOT RE 2; STOT SE 2<br><b>EU DSD/DPD:</b> R10Xn; R20Xi; R36/37/38N;<br>R51 R53 |
| Benzene, 1,3,5-<br>trimethyl                      | <b>CAS:</b> 108-67-8<br><b>EC Number:</b> 203-604-<br>4<br><b>UN:</b> UN2325<br><b>EINECS:</b> 203-604-4 | 0.5% TO<br>1.5% |  | <b>EU DSD/DPD:</b> R10 Xi; R37 N; R51 R53  |

**This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.**

See Section 11 for Toxicological Information.

#### Section 4 - First Aid Measures

- Inhalation** • IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. Get medical attention immediately.
- Skin** • IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
- Eye** • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Ingestion** • Call a physician or poison control center immediately. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Never give anything by mouth to an unconscious person.

See Section 2 for Potential Health Effects.

#### Section 5 - Fire Fighting Measures

- Extinguishing Media** • Use CO<sub>2</sub>, dry chemical, or foam.
- Unsuitable Extinguishing Media** • Do not use direct stream of water.
- Firefighting Procedures** • Fight advanced or massive fires from safe distance or protected location. Avoid water in a straight hose stream as the stream will cause splatter and spread fire. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and can be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

|   |   |
|---|---|
| <b>Unusual Fire and Explosion Hazards</b> | • Combustible liquid. May release irritating or toxic gases, fumes, or vapors.          |
| <b>Hazardous Combustion Products</b>      | • Carbon monoxide, carbon dioxide, hydrocarbons.  |
| <b>Protection of Firefighters</b>         | • Firefighters should wear self-contained breathing apparatus and full protective gear. |
| <b>Flash Point</b>                        | • 105°F(40.6°C) CC (Closed Cup)   |
| <b>Explosion Limits•</b>                  |   |
| <b>Upper</b>                              | • 6 %   |
| <b>Lower</b>                              | • 0.9 %   |
| <b>Autoignition Temperature</b>           | • No data available   |

## Section 6 - Accidental Release Measures

|                                      |   |
|--------------------------------------|---|
| <b>Personal Precautions</b>          | • Do not handle damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind. Ventilate the area before entry. Protect building inlet air when working around fresh air vents.                            |
| <b>Emergency Procedures</b>          | • ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Stop leak if you can do it without risk. Isolate the area and contain the spilled material. Product is a paste material which will have reduced flow. |
| <b>Environmental Precautions</b>     | • Prevent entry into waterways, sewers, basements or confined areas.  |
| <b>Containment/Clean-up Measures</b> | • Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. Use appropriate Personal Protective Equipment (PPE)   |
| <b>Prohibited Materials</b>          | • Avoid contact with strong oxidizing agents and acids.   |

## Section 7 - Handling and Storage

|   |  |
|---|--|
| <b>Handling</b>                                   | • KEEP OUT OF THE REACH OF CHILDREN! Keep away from heat, sparks, and flame – No Smoking. Use only with adequate ventilation. Protect building air inlets when using this product. |
| <b>Storage</b>                                    | • Store in a well-ventilated place. Keep container tightly closed. No open flames, no sparks and no smoking.   |
| <b>Special Packaging Materials</b>                | • No data available  |
| <b>Incompatible Materials or Ignition Sources</b> | • Avoid contact with strong oxidizing agents and acids.  |

## Section 8 - Exposure Controls/Personal Protection

### Personal Protective Equipment



|                    |   |
|--------------------|---|
| <b>Respiratory</b> | • In case of insufficient ventilation, wear suitable respiratory equipment. If listed exposure limits are expected to be exceeded, use approved respiratory protection suitable for the hazard. When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. |
| <b>Eye/Face</b>    | • Wear ANSI approved safety glasses with side shields or safety goggles.  |
| <b>Hands</b>       | • Wear chemical protective gloves made of Nitrile or Neoprene.  |
| <b>Skin/Body</b>   | • Wear clothing that covers the skin to prevent skin exposure.  |

**General Industrial Hygiene Considerations**

- Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling. Do not smoke, eat, or drink while using the product.

**Engineering Measures/Controls**

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

|                             | Result | ACGIH   | Canada Ontario  | OSHA   | United States - California   |
|-----------------------------|--------|---|---|--|--|
| Quartz (14808-60-7)         | TWAs   | 0.025 mg/m3 TWA (respirable fraction)   | 0.10 mg/m3 TWA (designated substance regulation, respirable)                | Not established  | 0.3 mg/m3 PEL (total dust); 0.1 mg/m3 PEL (respirable dust)  |
| Kaolin (1332-58-7)          | TWAs   | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) | 2 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, respirable) | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) | 2 mg/m3 PEL (respirable dust, containing no Asbestos fibers, <1% Crystalline silica)   |
| Cellulose (9004-34-6)       | TWAs   | 10 mg/m3 TWA  | 10 mg/m3 TWA  | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) | 5 mg/m3 PEL (respirable fraction, listed under Particulates not otherwise regulated); 10 mg/m3 PEL (total dust, listed under Particulates not otherwise regulated) |
| Mineral Spirits (8052-41-3) | TWAs   | 100 ppm TWA   | 525 mg/m3 TWA (140°C Flash aliphatic solvent)                               | 500 ppm TWA; 2900 mg/m3 TWA                                  | 100 ppm PEL; 525 mg/m3 PEL   |
| Asphalt (8052-42-4)         | TWAs   | 0.5 mg/m3 TWA (fume, inhalable fraction, as benzene soluble aerosol)                                    | 0.5 mg/m3 TWA (fume, inhalable, as Benzene-soluble aerosol)                 | Not established  | 5 mg/m3 PEL (fume)   |

**Exposure Control Notations**

**ACGIH**

- Kaolin (1332-58-7): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen)
- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free))
- Quartz (14808-60-7): **Carcinogens:** (A2 - Suspected Human Carcinogen)

**Key to abbreviations**

PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)

**Section 9 - Physical and Chemical Properties**

**Material Description**

|               |        |                                  |                          |
|---------------|--------|----------------------------------|--------------------------|
| Physical Form | Liquid | Appearance/Description           | Thick black semi-liquid. |
| Color         | Black  | Odor                             | Mild Hydrocarbon.        |
|               |        | Physical and Chemical Properties | Semi-liquid              |

**General Properties**

|               |                                  |                                   |              |
|---------------|----------------------------------|-----------------------------------|--------------|
| Boiling Point | 310 to 400° F(154.4 to 204.4° C) | Specific Gravity/Relative Density | 1.06 Water=1 |
| Density       | 9 lbs/gal                        |                                   |              |

**Volatility**

|                |                            |               |         |
|----------------|----------------------------|---------------|---------|
| Vapor Pressure | 2 mmHg (torr) @ 68 F(20 C) | Vapor Density | 1 Air=1 |
| VOC (Vol.)     | < 300 g/L                  |               |         |

**Flammability**

|             |                                  |     |     |
|-------------|----------------------------------|-----|-----|
| Flash Point | 105 F(40.5556 C) CC (Closed Cup) | UEL | 6 % |
| LEL         | .9 %                             |     |     |

**Section 10 - Stability and Reactivity**

**Stability**

- Stable under normal temperatures and pressures.

**Hazardous Polymerization**

- Hazardous polymerization not indicated.

**Conditions to Avoid**

- Avoid contact with strong oxidizing agents and flame.

**Incompatible Materials**

- Strong oxidizers.

**Hazardous Decomposition Products • Carbon monoxide, carbon dioxide and hydrocarbons.**

**Section 11 - Toxicological Information**

| Component Name   | CAS        | Data  |
|--|------------|---|
| Asphalt (40% TO 60%)                                   | 8052-42-4  | <b>Acute Toxicity:</b> orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3 |
| Cellulose (6% TO 10%)                                  | 9004-34-6  | <b>Acute Toxicity:</b> orl-rat LD50:>5 gm/kg                              |
| Solvent naphtha (petroleum), light aromatic (1% TO 5%) | 64742-95-6 | <b>Acute Toxicity:</b> orl-rat LD50:8400 mg/kg                            |
| 1,2,4-Trimethylbenzene (0.5% TO 1.5%)                  | 95-63-6    | <b>Acute Toxicity:</b> orl-rat LD50:5 gm/kg; ihl-rat LC50:18000 mg/m3/4H  |

**Other Component Information** • IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz. ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist. This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

**Section 12 - Ecological Information**

**Ecological Fate** • No data available.  
**Persistence/Degradability** • No data available.  
**Bioaccumulation Potential** • No data available.  
**Mobility in Soil** • No data available.

**Section 13 - Disposal Considerations**

**Product** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Section 14 - Transportation Information**

**DOT – Department of Transportation** - Not restricted if shipped in containers <450L (119 gallons) Restricted if shipped in containers >450L (119 gallons).

**TDG Transportation Other Information**•: Not Restricted under General Exemption for small container packaging.

**TDG - Canada Transportation of Dangerous Goods:** Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III 1.33 Class 3, Flammable Liquids

**IMO/IMDG –International Maritime Transport** • IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages. - Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III 1.33 Class 3, Flammable Liquids

**IATA - International Air Transport Association** - TARS, LIQUID; UN1999; Hazard Class: 3; Packing Group: III.

**Section 15 - Regulatory Information**

**SARA Hazard Classifications** • Acute, Chronic

**Risk & Safety Phrases** • California PROP 65: Asphalt and Asphalt Fumes may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

| State Right To Know                         |            |     |     |     |     |
|---|------------|-----|-----|-----|-----|
| Component                                   | CAS        | MA  | MN  | NJ  | PA  |
| Asphalt                                     | 8052-42-4  | Yes | Yes | Yes | Yes |
| Mineral Spirits                             | 8052-41-3  | Yes | Yes | Yes | Yes |
| Kaolin                                      | 1332-58-7  | Yes | Yes | Yes | Yes |
| Cellulose                                   | 9004-34-6  | Yes | Yes | Yes | Yes |
| Hydrated aluminum-magnesium silicate        | 12174-11-7 | No  | No  | No  | No  |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | No  | No  | No  | No  |
| Styrene/Butadiene Polymer                   | 9003-55-8  | No  | No  | No  | No  |
| Quartz                                      | 14808-60-7 | Yes | Yes | Yes | Yes |
| 1,2,4-Trimethylbenzene                      | 95-63-6    | Yes | Yes | Yes | Yes |
| Benzene, 1,3,5-trimethyl                    | 108-67-8   | Yes | No  | No  | No  |

| Inventory                                   |            |           |      |
|---|------------|-----------|------|
| Component                                   | CAS        | EU EINECS | TSCA |
| Asphalt                                     | 8052-42-4  | Yes       | Yes  |
| Mineral Spirits                             | 8052-41-3  | Yes       | Yes  |
| Kaolin                                      | 1332-58-7  | Yes       | Yes  |
| Cellulose                                   | 9004-34-6  | Yes       | Yes  |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | Yes       | Yes  |
| Styrene/Butadiene Polymer                   | 9003-55-8  | Yes       | Yes  |
| Quartz                                      | 14808-60-7 | Yes       | Yes  |
| 1,2,4-Trimethylbenzene                      | 95-63-6    | Yes       | Yes  |
| Benzene, 1,3,5-trimethyl                    | 108-67-8   | Yes       | Yes  |

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

|  |            |              |  |
|--|------------|--------------|--|
| •Kaolin                                      | 1332-58-7  | 5% TO 15%    | D2A  |
| •Cellulose                                   | 9004-34-6  | 6% TO 10%    | Uncontrolled product according to WHMIS classification criteria (including microcrystalline and paper fibers)  |
| •Asphalt                                     | 8052-42-4  | 40% TO 60%   | Not Listed   |
| •1,2,4-Trimethylbenzene                      | 95-63-6    | 0.5% TO 1.5% | B3   |
| •Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 1% TO 5%     | B3, D2B  |
| •Quartz                                      | 14808-60-7 | 1% TO 2%     | D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.) |
| •Mineral Spirits                             | 8052-41-3  | 15% TO 30%   | B3, D2B  |
| •Benzene, 1,3,5-trimethyl                    | 108-67-8   | 0.5% TO 1.5% | B3   |
| •Hydrated aluminum-magnesium silicate        | 12174-11-7 | 5% TO 10%    | Not Listed   |
| •Styrene/Butadiene Polymer                   | 9003-55-8  | 1% TO 5%     | Uncontrolled product according to WHMIS classification criteria  |

## United States

### Environment

#### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

|  |            |              |                                |
|--|------------|--------------|--------------------------------|
| •Kaolin                                      | 1332-58-7  | 5% TO 15%    | Not Listed                     |
| •Cellulose                                   | 9004-34-6  | 6% TO 10%    | Not Listed                     |
| •Asphalt                                     | 8052-42-4  | 40% TO 60%   | Not Listed                     |
| •1,2,4-Trimethylbenzene                      | 95-63-6    | 0.5% TO 1.5% | 1.0 % de minimis concentration |
| •Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 1% TO 5%     | Not Listed                     |
| •Quartz                                      | 14808-60-7 | 1% TO 2%     | Not Listed                     |
| •Mineral Spirits                             | 8052-41-3  | 15% TO 30%   | Not Listed                     |
| •Benzene, 1,3,5-trimethyl                    | 108-67-8   | 0.5% TO 1.5% | Not Listed                     |
| •Hydrated aluminum-magnesium silicate        | 12174-11-7 | 5% TO 10%    | Not Listed                     |
| •Styrene/Butadiene Polymer                   | 9003-55-8  | 1% TO 5%     | Not Listed                     |

## Section 16 - Other Information

Prepared By

- GG Inc.

Last Revision Date

- 1/11/2018

Disclaimer/Statement of Liability

- This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. The manufacturer does not accept liability for any loss or damage that may occur from the use of this information.

NFPA

