



# #3 Asphalt Primer Aerosol

## DATA SHEET

**COMPLIANCE:** Exceeds performance requirements of ASTM D41. Miami-Dade County Product Control Approved.

**DESCRIPTION:** Use TopShield #3 Asphalt Primer to prime newly laid concrete or cement decks, gypsum and masonry thermal insulation prior to applying built-up roofing. For weathered roofing, TopShield #3 can be used before applying built-up roofing, black coatings or reflective coatings. TopShield #3 improves adhesion.

**PREPARATION:** All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved Lion Guard Cement. DO NOT HEAT. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

**FOR BEST RESULTS:** Apply on clear sunny day when surface temperatures are between 35 °F and 120 °F. In colder weather product should be stored in heated room (65 °F to 80 °F) at least 24 hours prior to application.

**APPLICATION:** For exterior use only. Protective clothing, gloves, and eyewear should be used during application of these products. Surface must be clean and dry before painting. Protect surrounding areas from spray mist. For best result, use when can is between 50 °F and 90 °F. Shake can at least one minute after rattle is heard and occasionally during use. Spray surface with steady even strokes at a distance of 2 to 10 inches. Multiple coats may be applied, allowing 20 to 30 minutes between coats. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

**APPLICATION RATE:** Approximately 50 sq. ft. per can depending on porosity of surface and method of application. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS.

**CLEAN-UP:** Clean tools with paint thinner or mineral spirits.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	7.4 - 7.9 lbs.
Residue by Evaporation, %	60 min.
Consistency	Brush or Spray
Tack Time (50% Relative Humidity, 70 °F)	30 minutes
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

### Approx. Shipping Weights: (Note: All approx. weights include container)

17 oz spray can	1 lbs.
-----------------	--------

This product meets <0.70 MIR limit for aerosol primer category.

**STORAGE & HANDLING PRECAUTIONS:** Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety Data Sheets are available on the TopShield website at [www.srstopshield.com](http://www.srstopshield.com). You can also obtain a copy from your local TopShield Distributor or TopShield sales representative.

**WARRANTY AND DISCLAIMER:** To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Gardner-Gibson at (813) 248-2101 to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with Gardner-Gibson warranty procedures and program.

©2017 TopShield  
Manufactured by:  
Gardner-Gibson, Inc.  
P.O. Box 5449, Tampa, FL 33675  
See SDS for more information