



# #4 Roof Cement

## DATA SHEET

**COMPLIANCE:** Exceeds performance requirements of ASTM D4586. Miami-Dade County Product Control Approved.

**DESCRIPTION:** Use TopShield #4 Roof Cement for repair and in maintenance of shingles, tile roofs and asphalt-based roof systems, as well as to seal penetrations, valleys and edge metal. TopShield #4 may also be used to dampproof foundations.

**PREPARATION:** All surfaces must be clean, have proper drainage and be free of surface rust and any other foreign matter. **DO NOT HEAT OR THIN.**

**FOR BEST RESULTS:** Apply when surface temperatures are between 40 °F and 120 °F. In colder weather, product should be stored in heated room (65 °F to 80 °F.) at least 24 hours prior to application. Product formulated to be used year round. After a minimum of 90 days cure time, apply a reflective roof coating. This will greatly extend the life of the roof.

**APPLICATION:** For exterior use only. Product should be applied according to NRCA guidelines. Protective clothing and eye wear should be used during application of this product. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two or three inches beyond the problem area. Then embed a layer of reinforcing fabric into cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes and other projections meet the roof line.

**COVERAGE RATE:** Approximately 12 1/2 sq. ft. per gallon when applied 1/8" thick. Seal container when not in use.

**CLEAN-UP:** Clean tools with paint thinner or mineral spirits.

©2017 TopShield  
Manufactured by:  
Gardner-Gibson, Inc.  
P.O. Box 5449, Tampa, FL 33675  
See SDS for more information

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.4 - 8.9 lbs.
Combustible Solvents	Mineral Spirits
Consistency	Trowel
Application Temperatures	40 °F - 120 °F
Flammability	105 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

### Approx. Shipping Weights: (Note: All approx. weights include container)

3 gallons (11.4L)	28 lbs.
5 gallons (18.9L)	45 lbs.

**VOC: <250 g/L (regulatory)**

**STORAGE & HANDLING PRECAUTIONS:** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. Seal container when not in use.

**WARRANTY AND DISCLAIMER:** To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Gardner-Gibson at (813) 248-2101 to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with Gardner-Gibson warranty procedures and program.